



# Environmental Product Declaration



**Environmental Product Declaration for ready mix concrete products produced by JIBE Construcciones y Pavimentos S.A. de C.V. at their La Union facility in Coahuila**



## ADMINISTRATIVE INFORMATION

### International Certified Environmental Product Declaration

<b>Declared Product:</b>	This Environmental Product Declaration (EPD) covers ready mix concrete products produced by JIBE Construcciones y Pavimentos S.A. de C.V... Declared unit: 1 m3 of concrete
<b>Declaration Owner:</b>	JIBE Construcciones y Pavimentos S.A. de C.V.
	227 Calle Luis F. García, Ciudad Industrial Torreón
	Torreón, Coahuila
	www.jibeconstrucciones.com
<b>Program Operator:</b>	Labeling Sustainability
	Address, 11670 W Sunset Blvd.
	City, State, Los Angeles, CA
	www.labelingsustainability.com/
<b>Product Category Rule:</b>	Core PCR: ISO 21930:2017 Sustainability in buildings and civil engineering works – Core rules for environmental product declarations of construction products and services SubPCR: NSF International (March 2020). Product Category Rul (PCR) for Environmental Product Declarations (EPD) PCR for Concrete, v2.1
	Sub PCR Program Operator: NSF International
	Sub-category PCR review was conducted by: Thomas P. Gloria, Ph. D. of Industrial Ecology Consultants: 35 Bracebridge Rd., Newton, MA 02459-1728, t.gloria@industrial-ecology.com. Dr. Michael Overcash of Environmental Clarity: 2908 Chipmunk Lane, Raleigh, NC 27607-3117, mrovercash@earthlink.net. Mr. Bill Stough of Sustainable Research Group: PO Box 1684, Grand Rapids, MI 49501-1684, <a href="mailto:bstough@sustainableresearchgroup.com">bstough@sustainableresearchgroup.com</a> . Mr. Jack Geilbig, EcoForm: 2624 Abelia Way, Suite 611, Knoxville, TN 37931, <a href="mailto:jgeilbig@ecoform.com">jgeilbig@ecoform.com</a> .
<b>Independent LCA Reviewer and EPD Verifier:</b>	This EPD was independently verified in accordance with ISO 14025 and ISO 21930. The life cycle assessment was independently reviewed in accordance ISO 14044 and the referenced PCR.
	Independent verification of the declaration, according to ISO 14025:2006
	Internal <input type="checkbox"/> ; External X
	Third Party Verifier Geoffrey Guest, Certified 3rd Party Verifier under the International EPD Program ( <a href="http://www.environdec.com">www.environdec.com</a> ), CSA Group ( <a href="http://www.csaregistries.ca">www.csaregistries.ca</a> )
<b>Date of Issue:</b>	26 September 2023
<b>Period of Validity:</b>	5 years; valid until 26 September 2028
<b>EPD Number:</b>	1ebbd3ag-664f-4c85-00d3-7e4fc9a581a9





TABLE OF CONTENTS

**ADMINISTRATIVE INFORMATION ..... 1**

**COMPANY DESCRIPTION ..... 3**

**STUDY GOAL ..... 3**

**DESCRIPTION OF PRODUCT AND SCOPE ..... 3**

**READY MIX CONCRETE DESIGN SUMMARY ..... 4**

**READY MIX CONCRETE DESIGN COMPOSITION ..... 6**

**A1 RAW MATERIAL RECYCLED CONTENT AND MATERIAL LOSSES ..... 6**

**SYSTEM BOUNDARIES ..... 7**

**CUT-OFF CRITERIA ..... 9**

**DATA SOURCES AND DATA QUALITY ASSESSMENT ..... 9**

    Raw material transport:..... 10

    Electricity:..... 10

    Process/space heating: ..... 10

    Fuel required for machinery:..... 10

    Waste generation:..... 10

    Recovered energy:..... 10

    Recycled/reused material/components:..... 10

    Module A1 material losses:..... 10

    Direct A3 emissions accounting: ..... 10

    Waste transport requirements: ..... 10

    Product transport requirements:..... 10

**DATA QUALITY ASSESSMENT ..... 14**

**ENVIRONMENTAL INDICATORS AND INVENTORY METRICS ..... 15**

**TOTAL IMPACT SUMMARY ..... 18**

**ADDITIONAL ENVIRONMENTAL INFO ..... 23**

**REFERENCES ..... 23**

    ASTM Standards:..... 23

    CSA Standards:..... 24

    ISO Standards:..... 24

    EN Standards:..... 25

    Other References: ..... 25



## COMPANY DESCRIPTION

At Grupo JIBE we distinguish ourselves as a company with tradition and extensive experience. We are experts in civil engineering, urbanization, development of land roads, pavements, dirt roads and hydraulic infrastructure.

## STUDY GOAL

The intended application of this life cycle assessment (LCA) is to comply with the procedures for creating a Type III environmental product declaration (EPD) and publish the EPD for public review on the website, <http://labelingsustainability.com/>. This level of study is in accordance with EPD Product Category Rule (PCR) for Ready Mix Concrete published by NSF International (2019) and is a sub-PCR of International Standards Organization (ISO) 21930:2017 Sustainability in buildings and civil works - Core rules for EPDs of construction products and services; International Standards Organization (ISO) 14025:2006 Environmental labels and declarations, Type III environmental declarations-Principles and procedures; ISO 14044:2006 Environmental management, Life cycle assessment- Requirements and guidelines; and ISO 14040:2006 Environmental management, Life cycle assessment-Principles and framework. The performance of this study and its subsequent publishing is in alignment with the business-to-business (B2B) communication requirements for the environmental assessment of building products. The study does not intend to support comparative assertions and is intended to be disclosed to the public.

This project report was commissioned to differentiate JIBE Construcciones y Pavimentos S.A. de C.V. from their competition for the following reasons: generate an advantage for the organization; offer customers information to help them make informed product decisions; improve the environmental performance of JIBE Construcciones y Pavimentos S.A. de C.V. by continuously measuring, controlling and reducing the environmental impacts of their products; help project facilitators working on Leadership in Energy and Environmental Design (LEED) projects achieve their credit goal; and to strengthen JIBE Construcciones y Pavimentos S.A. de C.V.'s license to operate in the community. The intended audience for this LCA report is JIBE Construcciones y Pavimentos S.A. de C.V.'s employees, their suppliers, project specifiers of their products, architects, and engineers. The EPD report is also available for policy makers, government officials interested in sustainability, academic professors, and LCA professionals. This LCA report does not include product comparisons from other facilities.

## DESCRIPTION OF PRODUCT AND SCOPE

This EPD reports on 69 concrete mixes manufactured at the JIBE Construcciones y Pavimentos S.A. de C.V. La Unión concrete facility in Coahuila, México.

This LCA assumes the impacts from products manufactured in accordance with the standards outlined in this report. This LCA is a cradle-to-gate study, and therefore, stages extending beyond the plant gate are not included in this LCA. Excluded stages include transportation of the manufactured material to the construction site; on-site construction processes and components; building (infrastructure) use and maintenance; and "end-of-life" effects.



## READY MIX CONCRETE DESIGN SUMMARY

The following tables provide a list of the cement products considered in this EPD along with key performance parameters.

### All Declared Products

Table 1: All Declared products are considered in this environmental product declaration

Mix#	Unique name/ID	Short description	Product type	28 day strength, MPa	H2O to cement ratio
1	703507D2010	34.323275 MPa 28d strength Ready mix concrete	Ready mix concrete	34.32328	0.55
2	70350ND2010	34.323275 MPa 28d strength Ready mix concrete	Ready mix concrete	34.32328	0.6
3	70350NB2014	34.323275 MPa 28d strength Ready mix concrete	Ready mix concrete	34.32328	0.61
4	60300ND1010	29.41995 MPa 28d strength Ready mix concrete	Ready mix concrete	29.41995	0.38
5	70300ND2010	29.41995 MPa 28d strength Ready mix concrete	Ready mix concrete	29.41995	0.68
6	70300NB2014	29.41995 MPa 28d strength Ready mix concrete	Ready mix concrete	29.41995	0.65
7	723003D2010	29.41995 MPa 28d strength Ready mix concrete	Ready mix concrete	29.41995	0.52
8	703007D2014	29.41995 MPa 28d strength Ready mix concrete	Ready mix concrete	29.41995	0.6
9	723003D2014	29.41995 MPa 28d strength Ready mix concrete	Ready mix concrete	29.41995	0.53
10	70280NB2014	27.45862 MPa 28d strength Ready mix concrete	Ready mix concrete	27.45862	0.61
11	60280ND2018	27.45862 MPa 28d strength Ready mix concrete	Ready mix concrete	27.45862	0.61
12	70250ND2010	24.516625 MPa 28d strength Ready mix concrete	Ready mix concrete	24.51663	0.84
13	70250NB2014	24.516625 MPa 28d strength Ready mix concrete	Ready mix concrete	24.51663	0.82
14	60250ND2014	24.516625 MPa 28d strength Ready mix concrete	Ready mix concrete	24.51663	0.7
15	70250ND2014	24.516625 MPa 28d strength Ready mix concrete	Ready mix concrete	24.51663	0.83
16	70250RB2014	24.516625 MPa 28d strength Ready mix concrete	Ready mix concrete	24.51663	0.74
17	38250ND2014	24.516625 MPa 28d strength Ready mix concrete	Ready mix concrete	24.51663	0.63
18	40250NB1014	24.516625 MPa 28d strength Ready mix concrete	Ready mix concrete	24.51663	0.68
19	722503B2014	24.516625 MPa 28d strength Ready mix concrete	Ready mix concrete	24.51663	0.59
20	60250ND0514	24.516625 MPa 28d strength Ready mix concrete	Ready mix concrete	24.51663	0.81



21	70250RD2010	24.516625 MPa 28d strength Ready mix concrete	Ready mix concrete	24.51663	0.79
22	702507D2010	24.516625 MPa 28d strength Ready mix concrete	Ready mix concrete	24.51663	0.66
23	722503D2014	24.516625 MPa 28d strength Ready mix concrete	Ready mix concrete	24.51663	0.55
24	60250NB0514	24.516625 MPa 28d strength Ready mix concrete	Ready mix concrete	24.51663	0.82
25	60250NB2014	24.516625 MPa 28d strength Ready mix concrete	Ready mix concrete	24.51663	0.68
26	702507B2014	24.516625 MPa 28d strength Ready mix concrete	Ready mix concrete	24.51663	0.71
27	70250ND2018	24.516625 MPa 28d strength Ready mix concrete	Ready mix concrete	24.51663	0.75
28	722503D2010	24.516625 MPa 28d strength Ready mix concrete	Ready mix concrete	24.51663	0.58
29	71250NB1014	24.516625 MPa 28d strength Ready mix concrete	Ready mix concrete	24.51663	0.69
30	702507D2014	24.516625 MPa 28d strength Ready mix concrete	Ready mix concrete	24.51663	0.76
31	70250RD2014	24.516625 MPa 28d strength Ready mix concrete	Ready mix concrete	24.51663	0.77
32	71250ND1018	24.516625 MPa 28d strength Ready mix concrete	Ready mix concrete	24.51663	0.64
33	70210NB2014	20.593965 MPa 28d strength Ready mix concrete	Ready mix concrete	20.59397	0.82
34	70210RB2014	20.593965 MPa 28d strength Ready mix concrete	Ready mix concrete	20.59397	0.84
35	70210ND2010	20.593965 MPa 28d strength Ready mix concrete	Ready mix concrete	20.59397	0.88
36	70200ND2010	19.6133 MPa 28d strength Ready mix concrete	Ready mix concrete	19.6133	0.93
37	70200NB2014	19.6133 MPa 28d strength Ready mix concrete	Ready mix concrete	19.6133	0.87
38	70200ND2014	19.6133 MPa 28d strength Ready mix concrete	Ready mix concrete	19.6133	0.9
39	70200ND2010- A5	19.6133 MPa 28d strength Ready mix concrete	Ready mix concrete	19.6133	0.85
40	70200RB2014	19.6133 MPa 28d strength Ready mix concrete	Ready mix concrete	19.6133	0.86
41	71200NB1014	19.6133 MPa 28d strength Ready mix concrete	Ready mix concrete	19.6133	0.77
42	702007B2014	19.6133 MPa 28d strength Ready mix concrete	Ready mix concrete	19.6133	0.81
43	722003D2010	19.6133 MPa 28d strength Ready mix concrete	Ready mix concrete	19.6133	0.63
44	70150ND2010	14.709975 MPa 28d strength Ready mix concrete	Ready mix concrete	14.709975	1.14
45	70150ND2010- A5	14.709975 MPa 28d strength Ready mix concrete	Ready mix concrete	14.709975	1
46	70150NB2014	14.709975 MPa 28d strength Ready mix concrete	Ready mix concrete	14.709975	1.02



47	70150ND2014	14.709975 MPa 28d strength Ready mix concrete	Ready mix concrete	14.709975	1.08
48	71150ND1018	14.709975 MPa 28d strength Ready mix concrete	Ready mix concrete	14.709975	0.81
49	71150ND1010	14.709975 MPa 28d strength Ready mix concrete	Ready mix concrete	14.709975	0.92
50	71150NB1014	14.709975 MPa 28d strength Ready mix concrete	Ready mix concrete	14.709975	0.87
51	70100ND2010	9.80665 MPa 28d strength Ready mix concrete	Ready mix concrete	9.80665	1.28
52	73100NB0514	9.80665 MPa 28d strength Ready mix concrete	Ready mix concrete	9.80665	1.09
53	73050NB0514	4.903325 MPa 28d strength Ready mix concrete	Ready mix concrete	4.903325	1.42
54	19050ND2010	4.903325 MPa 28d strength Ready mix concrete	Ready mix concrete	4.903325	0.6
55	73050ND0510	4.903325 MPa 28d strength Ready mix concrete	Ready mix concrete	4.903325	1.44
56	77045ND4010	4.4129925 MPa 28d strength Ready mix concrete	Ready mix concrete	4.412992	0.69
57	770451D4010	4.4129925 MPa 28d strength Ready mix concrete	Ready mix concrete	4.412992	0.46
58	77042NB2014	4.118793 MPa 28d strength Ready mix concrete	Ready mix concrete	4.118793	0.7
59	77042ND4010	4.118793 MPa 28d strength Ready mix concrete	Ready mix concrete	4.118793	0.72
60	77042ND2010	4.118793 MPa 28d strength Ready mix concrete	Ready mix concrete	4.118793	0.71
61	77040ND4010	3.92266 MPa 28d strength Ready mix concrete	Ready mix concrete	3.92266	0.68
62	77040ND4014	3.92266 MPa 28d strength Ready mix concrete	Ready mix concrete	3.92266	0.67
63	77040ND2014	3.92266 MPa 28d strength Ready mix concrete	Ready mix concrete	3.92266	0.64
64	77038ND2014	3.726527 MPa 28d strength Ready mix concrete	Ready mix concrete	3.726527	0.79
65	77038NB2014	3.726527 MPa 28d strength Ready mix concrete	Ready mix concrete	3.726527	0.73
66	24025ND0514	2.4516625 MPa 28d strength Ready mix concrete	Ready mix concrete	2.451662	1.93
67	24020NB0518	1.96133 MPa 28d strength Ready mix concrete	Ready mix concrete	1.96133	2.78
68	24020ND0514	1.96133 MPa 28d strength Ready mix concrete	Ready mix concrete	1.96133	1.93
69	24015NB0514	1.4709975 MPa 28d strength Ready mix concrete	Ready mix concrete	1.470997	2.8

## READY MIX CONCRETE DESIGN COMPOSITION

The following figures provide mass breakdown (kg per functional unit) of the material composition of each ready mix concrete design considered. Please note that the presented breakdown has been



randomly altered by +/-10%, and is therefore only an approximation; this manipulation is to ensure confidentiality.

Table 2: Ready mix concrete composition

Product Components	Raw Material, weight%
Cement	Proprietary
Aggregates	30-60.00
Others	0.01-5.00
Total	100.00

## A1 RAW MATERIAL RECYCLED CONTENT AND MATERIAL LOSSES –

The following table provides a list of the raw material inputs (module A1) across all products considered, their recyclability content and assumed material losses.

Table 3: Module A1 raw material inputs, the recyclability content and assumed material losses (dry basis)

product.name	mix.category	primary.content	post.industrial.content	post.consumer.content	material.losses
Cement CPC 40	cement, unspecified	1	0	0	0
Water	tap water	1	0	0	0.05
Limestone	limestone, unprocessed	1	0	0	0.05
Sand	sand	1	0	0	0.05
Additives	chemical, organic	1	0	0	0.05
Ash	cement, pozzolana and fly ash 36-55%	1	0	0	0.05
Additives	chemical, organic	1	0	0	0.05

## SYSTEM BOUNDARIES

The following figure depicts the cradle-to-gate system boundary considered in this study:





### Life Cycle Impacts

<p>A1-A3 <b>PRODUCT STAGE</b></p> <p>A1 Raw material supply A2 Transport A3 Manufacturing</p>	<p>A4-A5 <b>INSTALLATION PROCESS STAGE</b></p> <p>A4 Transport to site A5 Installation Process</p>	<p>B1-B7 <b>USE STAGE</b></p> <p>B1 Use B2 Maintenance B3 Repaired B4 Replacement B5 Refurbishment B6 Operational energy use B7 Operational water use</p>	<p>C1-C4 <b>END OF LIFE STAGE</b></p> <p>C1 De-installation/ Demolition C2 Transport C3 Waste processing C4 Disposal of Waste</p>
<b>X</b>	<b>ND</b>	<b>ND</b>	<b>ND</b>

Figure 1: General life cycle phases for consideration in a construction works system

This is a Cradle-to-gate life cycle assessment and the following life cycle stages are included in the study:

- A1: Raw material supply (upstream processes) - Extraction, handling, and processing of the materials used in manufacturing the declared products in this LCA.
- A2: Transportation - Transportation of A1 materials from the supplier to the “gate” of the manufacturing facility (i.e. A3).
- A3: Manufacturing (core processes)- The energy and other utility inputs used to store, move, and manufacturer the declared products and to operate the facility.

As according to the PCR, the following figure illustrates the general activities and input requirements for producing cement products and is not necessarily exhaustive.

### System Boundary

<p>Raw Material Supply <b>(A1)</b></p> <p>Cements &amp; SCMs Aggregates Admixtures Batch Water Fibers &amp; Pigments</p>	<p>Transport <b>(A2)</b></p> <p>Truck, Rail, Ship Energy Carriers (fuels)</p>	<p>Manufacturing <b>(A3)</b></p> <p>Energy Carriers (electricity and fuels) Ancillary Materials (lubricants, motor oil, cleaning chemicals, other consumables) Water (manufacturing water, including wash water for cement trucks, but excluding batch water) Waste (end of life treatment of ancillary materials and any packaging) 30% total fleet energy transit mix plants only</p>
----------------------------------------------------------------------------------------------------------------------------------------------	---------------------------------------------------------------------------------------	-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

Figure 2: General system inputs considered in the product system and categorized by modules in scope

In addition, as according to the relevant PCR, the following requirements are excluded from this study:

- Production, manufacture, and construction of A3 building/capital goods and infrastructure.
- Production and manufacture of steel production equipment, steel delivery vehicles, earth-moving equipment, and laboratory equipment.
- Personnel-related activities (travel, furniture, office supplies).



- Energy use related to company management and sales activities.

For this LCA the manufacturing plant, owned and operated by JIBE Construcciones y Pavimentos S.A. de C.V., is located at their Planta La Union facility in Mexico. All operating data is formulated using the actual data from JIBE Construcciones y Pavimentos S.A. de C.V.'s plant at the above location, including water, energy consumption and waste generation. All inputs for this system boundary are calculated for the plant.

This life cycle inventory was organized in a spreadsheet and was then input into an RStudio environment where pre-calculated LCIA results for relevant products/activities stemming from the ecoinvent ecoinvent v3.8 database and a local EPD database in combination with primary data from JIBE Construcciones y Pavimentos S.A. de C.V. were utilized. Explanations of the contribution of each data source to this study are outlined in the section 'Data Sources and Quality'. Further LCI details for each declared product are provided in the sections 'Detailed LCI tables' and 'Transport tables' of the detailed LCA report. A parameter uncertainty analysis was also performed where key statistical results (e.g. min/mean/max etc.) are provided in the detailed LCA report.

## CUT-OFF CRITERIA

ISO 14044:2006 and the focus PCR requires the LCA model to contain a minimum of 95% of the total inflows (mass and energy) to the upstream and core modules be included in this study. The cut-off criteria were applied to all other processes unless otherwise noted above as follows. A 1% cut-off is considered for all renewable and non-renewable primary energy consumption and the total mass of inputs within a unit process where the total of the neglected inputs does not exceed 5%.

## DATA SOURCES AND DATA QUALITY ASSESSMENT

The following table summarizes the facility's (i.e. A3) electricity consumption and on-site generation or off-site contractual procurement (if applicable), process/space heating requirements, fuel inputs for on-site machinery, and waste generation.

Table 4: Inputs required by facility from 2023-02-01 to 2023-02-28 (364 days) to produce 26,780 m3 of concrete

Activity	Value	Units
<b>Electricity consumption and on-site generation or off-site contractual procurement (if applicable)</b>		
Gross grid electricity:	46,513	kWh
<b>Fuel requirements for machinery</b>		
Diesel	6,952	L
<b>Waste generation</b>		
Wash water	1,700	m3
Hazardous waste	400	kg
Non-hazardous waste	20,000	kg
High-level radioactive waste	0	kg

No recovered on-site energy occurs at this facility.

Table 5: Reused or recycled components/materials at the A3 facility site





Component/material for re-use/recycling	Value	Units	Re-used/recycled on-site or off-site
Returned concrete	17.5	m3	On-Site

The following statements explain how the above facility requirements/generation were derived:

**Raw material transport:** A combination of actual mode/distance combinations were assumed for key bulk materials whereasecoinvent default multi-modal market mix distances were assumed for other inputs where no original data could be provided.

**Electricity:** Electricity consumption values are for JIBE Construcciones y Pavimentos S.A. de C.V. in calendar year 2022. These values were direct reported from JIBE records. The unit process "market for electricity, medium voltage/electricity, medium voltage/MX/kWh" was used to represent the Mexico grid electricity used by the concrete plant.

**Process/space heating:** No fuel is used for space Heating at this plant.

**Fuel required for machinery:** Machinery-related fuel requirements were determined from direct JIBE information. The types of machinery used include generators, pumps to pump concrete to higher elevations, and transportation equipment used for moving materials.

**Waste generation:** Waste generation values are directly reported from JIBE operations for both bulk waste and hazardous waste. No High-level radioactive waste is generated on-site at this facility. Wash water for trucks was also primary reported data for 2022.

**Recovered energy:** Not applicable.

**Recycled/reused material/components:** The amount of returned concrete is based on JIBE primary data for the reference year, 2022.

**Module A1 material losses:** Due to lack of data, default loss factors of 5% were assumed. The PCR states " A3 shall include an assumption of 5% material loss unless product specific data is available and transparently reported in the project LCA report underlying the EPD;".

**Direct A3 emissions accounting:** Direct emissions are modeled using fuel and technology appropriateecoinvent activities. See LCI input tables for details.

**Waste transport requirements:** Transportation distances are using estimated values. The waste hauler cannot guarantee the exact distances traveled due to the variation of route and actual location of disposal. Most waste disposal sites are near the plant therefore the 25 km distance is a representative estimate. Returned concrete and wash water, measured in kilograms, is based on direct JIBE reporting for the reference year 2022.

**Product transport requirements:** The diesel fuel used by the mixing trucks is direct primary information reported from JIBE records for the year 2022. The concrete PCR allots 30% of the overall mixing truck total for stage A3 (manufacturing) for mixing the materials.



The following tables depict a list of assumed life cycle inventory utilized in the LCA modeling to generate the impact results across the life cycle modules in scope. An assessment of the quality of each LCI activities utilized from various sources is also provided.

Table 6: LCI inputs assumed for module A1 (i.e. raw material supply) Data Quality Assessment Key Fair=1, Good=2, Very Good =3.

Input	LCI.activity	Data.source	Geo	Year	Technology	Time	Geography	Reliability	Completeness
Water	tap water production, conventional with biological treatment/tap water/RoW/kg	ecoinvent v3.8	Coahuila	v3.8 in 2021	2	3	1	3	3
Limestone	limestone quarry operation/limestone, unprocessed/RoW/kg; Note: modifications made (see ecoinvent activity changes table)	ecoinvent v3.8	Coahila	v3.8 in 2021	2	3	1	3	3
Additives	market for chemical, organic/chemical, organic/GLO/kg	ecoinvent v3.8	Coahuila	v3.8 in 2021	2	3	1	3	3
Cement CPC 40	CPC 40	Progam Operator: Labeling Sustainability-EPD ID: ab22ee19-4f97-41a2-bf8a-4297c635a5d6	Coahuila	very good, 3rd party verified facility-specific EPD dataset	3	NA	3	3	3
Sand	sand quarry operation, extraction from river bed/sand/BR/kg; Note: modifications made (see ecoinvent activity changes table)	ecoinvent v3.8	Coahila, Durango	v3.8 in 2021	2	3	1	3	3
Ash	Waste input produced off-site	See A3 inputs	Coahila	See A3 inputs	2	A3	1	A3	A3

Table 7: LCI inputs assumed for module A2 (i.e. transport of A1 inputs)

Input	LCI.activity	Data.source	Geo	Year	Technology	Time	Geography	Reliability	Completeness
-------	--------------	-------------	-----	------	------------	------	-----------	-------------	--------------



<b>Additives- freight transport via Truck</b>	market for transport, freight, lorry 7.5-16 metric ton, EURO6/transport, freight, lorry 7.5-16 metric ton, EURO6/RoW/tkm	ecoinvent v3.8	RoW	v3.8 in 2021		2	3	1	3	3
<b>Ash- freight transport via Truck</b>	market for transport, freight, lorry 7.5-16 metric ton, EURO6/transport, freight, lorry 7.5-16 metric ton, EURO6/RoW/tkm	ecoinvent v3.8	RoW	v3.8 in 2021		2	3	1	3	3
<b>Cement CPC 40- freight transport via Truck</b>	market for transport, freight, lorry 7.5-16 metric ton, EURO6/transport, freight, lorry 7.5-16 metric ton, EURO6/RoW/tkm	ecoinvent v3.8	RoW	v3.8 in 2021		2	3	1	3	3
<b>Limestone- freight transport via Truck</b>	market for transport, freight, lorry 7.5-16 metric ton, EURO6/transport, freight, lorry 7.5-16 metric ton, EURO6/RoW/tkm	ecoinvent v3.8	RoW	v3.8 in 2021		2	3	1	3	3
<b>Sand- freight transport via Truck</b>	market for transport, freight, lorry 7.5-16 metric ton, EURO6/transport, freight, lorry 7.5-16 metric ton, EURO6/RoW/tkm	ecoinvent v3.8	RoW	v3.8 in 2021		2	3	1	3	3

Table 8: LCI inputs assumed for module A3

Input	LCI.activity	Data.source	Geo	Year	Technology	Time	Geography	Reliability	Completeness
-------	--------------	-------------	-----	------	------------	------	-----------	-------------	--------------



<b>Diesel</b>	diesel, burned in building machine/diesel, burned in building machine/GLO/MJ	ecoinvent v3.8	GLO	v3.8 in 2021	2	3	1	3	3
<b>Diesel used for mixing trucks</b>	transport, freight, lorry 7.5-16 metric ton, EURO6/transport, freight, lorry 7.5-16 metric ton, EURO6/RoW/tkm	ecoinvent v3.8	RoW	v3.8 in 2021	2	3	2	3	3
<b>Grid electricity</b>	market for electricity, medium voltage/electricity, medium voltage/SV/kWh	ecoinvent v3.8	SV	v3.8 in 2021	3	3	3	3	3
<b>Hazardous waste</b>	treatment of hazardous waste, hazardous waste incineration/hazardous waste, for incineration/RoW/kg	ecoinvent v3.8	RoW	v3.8 in 2021	2	3	1	3	3
<b>Non-hazardous waste</b>	treatment of municipal solid waste, sanitary landfill/municipal solid waste/RoW/kg	ecoinvent v3.8	RoW	v3.8 in 2021	1	3	1	3	3
<b>Transport of Hazardous waste</b>	transport, freight, lorry, all sizes, EURO4 to generic market for transport, freight, lorry, unspecified/transport, freight, lorry, unspecified/RoW/tkm	ecoinvent v3.8	RoW	v3.8 in 2021	2	3	1	3	3k
<b>Transport of Non-hazardous waste</b>	transport, freight, lorry, all sizes, EURO5 to generic market for transport, freight, lorry, unspecified/transport, freight, lorry, unspecified/RoW/tkm	ecoinvent v3.8	RoW	v3.8 in 2021	2	3	1	3	3
<b>Transport of Returned concrete</b>	transport, freight, lorry >32 metric ton, EURO6/transport, freight, lorry >32 metric ton, EURO6/RoW/tkm	ecoinvent v3.8	RoW	v3.8 in 2021	2	3	1	3	3
<b>Transport of Wash water</b>	transport, freight, lorry >32 metric ton, EURO6/transport, freight, lorry >32 metric ton, EURO6/RoW/tkm	ecoinvent v3.8	RoW	v3.8 in 2021	2	3	1	3	3
<b>Wash water</b>	tap water production, conventional with	ecoinvent v3.8	RoW	v3.8 in 2021	2	3	1	3	3





biological treatment/tap water/RoW/kg									
---------------------------------------	--	--	--	--	--	--	--	--	--

## DATA QUALITY ASSESSMENT

Data quality/variability requirements, as specified in the PCR, are applied. This section describes the achieved data quality relative to the ISO 14044:2006 requirements. Data quality is judged based on its precision (measured, calculated, or estimated), completeness (e.g., unreported emissions), consistency (degree of uniformity of the methodology applied within a study serving as a data source) and representativeness (geographical, temporal, and technological).

**Precision:** Through measurement and calculation, the manufacturers collected and provided primary data on their annual production. For accuracy, the LCA practitioner and 3rd Party Verifier validated the plant gate-to-gate data.

**Completeness:** All relevant specific processes, including inputs (raw materials, energy, and ancillary materials) and outputs (emissions and production volume) were considered and modeled to represent the specified and declared products. The majority of relevant background materials and processes were taken from ecoinvent v3.8 LCI datasets where relatively recent region-specific electricity inputs were utilized. The most relevant EPDs requiring key A1 inputs were also utilized where readily available.

**Consistency:** To ensure consistency, the same modeling structure across the respective product systems was utilized for all inputs, which consisted of raw material inputs and ancillary material, energy flows, water resource inputs, product, and co-products outputs, returned and recovered Ready mix Concrete materials, emissions to air, water and soil, and waste recycling and treatment. The same background LCI datasets from the ecoinvent v3.8 database were used across all product systems. Crosschecks concerning the plausibility of mass and energy flows were continuously conducted. The LCA team conducted mass and energy balances at the plant and selected process level to maintain a high level of consistency.

**Reproducibility:** Internal reproducibility is possible since the data and the models are stored and available in a machine readable project file for all foreground and background processes, and in Labeling Sustainability's proprietary Ready Mix Concrete LCA calculator\* for all production facility and product-specific calculations. A considerable level of transparency is provided throughout the detailed LCA report as the specifications and material quantity make-up for the declared products are presented and key primary and secondary LCI data sources are summarized. The provision of more detailed publicly accessible data to allow full external reproducibility was not possible due to reasons of confidentiality.

\*Labeling Sustainability has developed a proprietary tool that allows the calculation of PCR-compliant LCA results for Ready Mix Concrete product designs. The tool auto-calculates results by scaling base-unit technosphere inputs (i.e. 1 kg sand, 1 kWh electricity, etc.) to replicate the reference flow conversions that take place in any typical LCA software like openLCA or SimaPro. The tool was tested against several LCAs performed in openLCA and the tool generated identical results to those realized in openLCA across every impact category and inventory metric (where comparisons could be readily made).



**Representativeness:** The representativeness of the data is summarized as follows.

- Time related coverage of the manufacturing processes' primary collected data from 2023-02-01 to 2023-02-28.
- Upstream (background) LCI data was either the PCR specified default (if applicable) or more appropriate LCI datasets as found in the country-adjusted ecoinvent v3.8 database.
- Geographical coverage for inputs required by the A3 facility(ies) is representative of its region of focus; other upstream and background processes are based on US, North American, or global average data and adjusted to regional electricity mixes when relevant.
- Technological coverage is typical or average and specific to the participating facilities for all primary data.

## ENVIRONMENTAL INDICATORS AND INVENTORY METRICS

Per the PCR, this EPD supports the life cycle impact assessment indicators and inventory metrics as listed in the tables below. As specified in the PCR, the most recent US EPA Tool for the Reduction and Assessment of Chemical and Other Environmental Impacts (TRACI), impact categories were utilized as they provide a North American context for the mandatory category indicators to be included in the EPD. Additionally, the PCR requires a set of inventory metrics to be reported with the LCIA indicators (see tables below).

Table 10: Life cycle impact categories and life cycle inventory metrics

ID	LCIA.indicators	Abbreviations	Units
1	environmental impact: acidification	AP	moles of H <sup>+</sup> -Eq
2	environmental impact: eutrophication	EP	kg N
3	environmental impact: global warming	GWP	kg CO <sub>2</sub> -Eq
4	environmental impact: ozone depletion	ODP	kg CFC-11-Eq
5	environmental impact: photochemical oxidation	PCOP	kg NO <sub>x</sub> -Eq
6	material resources: metals/minerals: abiotic depletion potential (ADP): elements (ultimate reserves)	ADPe	kg Sb-Eq
7	energy resources: non-renewable: abiotic depletion potential (ADP): fossil fuels	ADPf	MJ, net calorific value
<b>Inventory metrics</b>			
8	Total primary energy	TPE	MJ-Eq
9	Renewable energy	RE	MJ-Eq
10	Non-renewable energy	NRE	MJ-Eq
11	Non-Renewable Resources	NRR	kg
12	Renewable Resources	RR	m <sup>3</sup>
13	water depletion: WDP	WDP	m <sup>3</sup>
14	land filling: bulk waste	LFW	kg waste
15	land filling: hazardous waste	LFHW	kg waste
16	Concrete batching water consumption	CBWC	m <sup>3</sup>
17	Concrete washing water consumption	CW/WC	m <sup>3</sup>
18	Concrete hazardous waste	CHW	kg
19	Concrete non-hazardous waste	CNHW	kg





A summary description of each of the impact categories and inventory metrics is provided in the following table:

Table 11: **Definitions of life cycle impact categories and life cycle inventory metrics**

<b>Midpoint impact categories</b>	
<b>Global Warming Potential (GWP) (units: kg CO<sub>2</sub>-eq)</b>	Global Warming Potential or climate change can be defined as the change in global temperature caused by the greenhouse effect that the release of greenhouse gases by human activity creates. The Environmental Profiles characterization model is based on factors developed by the United Nations Intergovernmental Panel on Climate Change (IPCC). Factors are expressed as Global Warming Potential over the time horizon of different years, being the most common 100 years (GWP <sub>100</sub> ), measured in the reference unit, kg CO <sub>2</sub> equivalent.
<b>Ozone Depletion Potential (ODP) (kg CFC-11-eq)</b>	Ozone-depleting gases cause damage to stratospheric ozone or the ozone layer. CFCs, halons and HCFCs are the major causes of ozone depletion. The characterization model has been developed by the World Meteorological Organization (WMO) and defines the ozone depletion potential of different gases relative to the reference substance chlorofluorocarbon-11 (CFC-11), expressed in kg CFC-11 equivalent.
<b>Acidification Potential (AP) (kg SO<sub>2</sub>-eq)</b>	Acidic gases such as Sulphur dioxide (SO <sub>2</sub> ) react with water in the atmosphere to form acid rain, a process known as acid deposition. Acidification potential is expressed using the reference unit, kg SO <sub>2</sub> equivalent. The model does not take account of regional differences in terms of which areas are more or less susceptible to acidification. It accounts only for acidification caused by SO <sub>2</sub> and NO <sub>x</sub> . This includes acidification due to fertilizer use, according to the method developed by the Intergovernmental Panel on Climate Change (IPCC). CML has based the characterization factor on the RAINS model developed by the University of Amsterdam.
<b>Eutrophication Potential (EP) (PO<sub>4</sub> 3- -eq)</b>	Eutrophication is the build-up of a concentration of chemical nutrients in an ecosystem which leads to abnormal productivity. This causes excessive plant growth like algae in rivers which causes severe reductions in water quality and animal populations. This category is based on the work of Heijungs, and is expressed using the reference unit, kg PO <sub>4</sub> 3- equivalents. Direct and indirect impacts of fertilizers are included in the method. The direct impacts are from production of the fertilizers and the indirect ones are calculated using the IPCC method to estimate emissions to water causing eutrophication.
<b>Photochemical Ozone Creation/Smog Potential (POCP) (kg O<sub>3</sub>-eq)</b>	Ozone is protective in the stratosphere, but on the ground-level, it is toxic to humans in high concentration. Photochemical ozone, also called ground-level ozone, is formed by the reaction of volatile organic compounds and nitrogen oxides in the presence of heat and sunlight. The impact category depends largely on the amounts of carbon monoxide (CO), Sulphur dioxide (SO <sub>2</sub> ), nitrogen oxide (NO), ammonium and NMVOC (non-methane volatile organic compounds). Photochemical ozone creation potential (also known as summer smog) for emission of substances to air is calculated with the United Nations Economic Commission for 22 Europe (UNECE) trajectory model (including fate) and expressed using the reference unit, kg ethylene (C <sub>2</sub> H <sub>4</sub> ) equivalent.
<b>Abiotic Depletion Potential (ADPeI and ADPff) (kg Sb-eq)</b>	The main concern of this category is the health of humans and the ecosystem and how it is affected by the extraction of minerals and fossil fuels, which are inputs into the system. For each extraction of minerals and

	fossil fuels, the abiotic depletion factor is determined. This indicator is on a global scale and is based on the concentration reserves and rate of deaccumulation. The results are presented in units of the reference element strontium (i.e. Sb). For the purposes of this EPD, this impact category is split between mineral elements (i.e. ADPeI) and fossil fuels (i.e. ADPff).
<b>Inventory metrics</b>	
<b>Depletion of non-renewable material resources (NRM) (kg)</b>	This indicator covers the cumulative life cycle consumption of non-renewable resources that are extracted from the ground but not including energy resources like coal, oil and natural gas. This indicator includes the consumption of metallic ores, aggregates, and other minerals. The units of measure are in terms of kilograms material extracted and utilized/wasted in the life cycle system considered.
<b>Use of renewable material resources (RM) (kg)</b>	This indicator covers the cumulative life cycle consumption of renewable resources that are extracted from nature like sustainably harvested biomass. The units of measure are in terms of kilograms material extracted and utilized/wasted in the life cycle system considered.
<b>Depletion of non-renewable energy resources (NRE) (MJ HHV)</b>	This indicator considers the cumulative life cycle consumption of non-renewable energy resources like oil, natural gas, and coal. The units of measure are in terms of Mega-Joules of energy resource extracted and utilized/wasted in the life cycle system considered.
<b>Use of renewable primary energy (RE) (MJ HHV)</b>	This indicator considers the cumulative life cycle extraction of renewable energy resources from nature like solar and wind energy as well as biomass for energy purposes. The units of measure are in terms of Mega-Joules of energy resource extracted and utilized/wasted in the life cycle system considered.
<b>Total primary energy consumption (PEC) (MJ HHV)</b>	This indicator is the summation of non-renewable and renewable energy extracted from nature, where the units of measure are in terms of Mega-Joules of energy resource extracted/used/wasted in the life cycle system considered.
<b>Water Depletion Potential (WDP) (m<sup>3</sup>)</b>	This indicator considers the cumulative life cycle consumption of water required to produce the declared functional unit of a given product. The units of measure are in cubic meters of water consumed.
<b>Concrete batching water consumption (CBWC) (m<sup>3</sup>)</b>	This indicator is defined as the direct water used in concrete mix batches. The units of measure are in cubic meters of water consumed.
<b>Concrete washing water consumption (CWWC) (m<sup>3</sup>)</b>	This indicator is defined as the direct washing water used at the facility. The units of measure are in cubic meters of wash water consumed.
<b>Concrete hazardous waste (CHW) (kg)</b>	This indicator considers the amount of hazardous waste generated at the concrete facility. The units of measure are in kilograms of waste generated.
<b>Concrete non-hazardous waste (CNHW) (kg)</b>	This indicator considers the direct amount of non-hazardous waste generated at the concrete facility. The units of measure are in kilograms of waste generated.

It should be noted that emerging LCA impact categories and inventory items are still under development and can have high levels of uncertainty that preclude international acceptance pending further development. Use caution when interpreting data in any of the following categories.

- Renewable primary energy resources as energy (fuel);
- Renewable primary resources as material;
- Non-renewable primary resources as energy (fuel);

- Non-renewable primary resources as material;
- Secondary Materials;
- Renewable secondary fuels;
- Non-renewable secondary fuels;
- Recovered energy;
- Abiotic depletion potential for non-fossil mineral resources.
- Land use related impacts, for example on biodiversity and/or soil fertility;
- Toxicological aspects;
- Emissions from land use change [GWP 100 (land-use change)];
- Hazardous waste disposed;
- Non-hazardous waste disposed;
- High-level radioactive waste;
- Intermediate and low-level radioactive waste;
- Components for reuse;
- Materials for recycling;
- Materials for energy recovery;
- Recovered energy exported from the product system.

## TOTAL IMPACT SUMMARY

The following table reports the total LCA results for each product produced at the given ready mix concrete facility on a per 1m<sup>3</sup> of concrete basis.

### All Declared Products

Table 12: **Total life cycle (across modules in scope) impact results for all declared products, assuming the geometric mean point values on a per 1 m<sup>3</sup> of concrete basis.**

#### a) Midpoint Impact Categories:

Indicator/LCI Metric	AP	EP	GWP	ODP	PCOP	ADPe	ADPf
Unit	moles of H <sup>+</sup> -Eq	kg N	kg CO <sub>2</sub> -Eq	kg CFC-11-Eq	kg NO <sub>x</sub> -Eq	kg Sb-Eq	MJ, net calorific value
Minimum	16.2	0.026	108	1.01E-05	0.255	0.000375	807
<b>Maximum</b>	<b>46.6</b>	<b>0.0701</b>	<b>384</b>	<b>2.84E-05</b>	<b>0.676</b>	<b>0.0013</b>	<b>2250</b>
Mean	33.6	0.0512	262	2.04E-05	0.496	0.000892	1590
Median	33.9	0.0517	264	2.06E-05	0.501	9.00E-04	1610
770451D4010	46.6	0.0701	384	2.84E-05	0.676	0.0013	2250
723003D2014	44.8	0.0672	363	2.69E-05	0.655	0.00123	2130
60300ND1010	43.6	0.0649	360	2.59E-05	0.631	0.0012	1970
722503D2014	43.8	0.0657	355	2.63E-05	0.639	0.0012	2090
703507D2010	43.3	0.0653	352	2.64E-05	0.631	0.00119	2070
60250NB0514	42.8	0.0646	351	2.62E-05	0.634	0.00116	2050
723003D2010	43.2	0.065	350	2.61E-05	0.635	0.00117	2060
40250NB1014	41.8	0.0628	347	2.54E-05	0.613	0.00115	1990
60250ND0514	42	0.0634	345	2.58E-05	0.622	0.00113	2000
70350NB2014	41.4	0.0625	336	2.52E-05	0.604	0.00113	1980



722503B2014	41.5	0.0625	335	2.49E-05	0.608	0.00113	1980
19050ND2010	41.2	0.0623	329	2.50E-05	0.602	0.00113	2000
722503D2010	40.2	0.0605	322	2.41E-05	0.59	0.00109	1910
70350ND2010	39.9	0.0603	322	2.43E-05	0.584	0.00109	1900
70300NB2014	39	0.0589	313	2.37E-05	0.571	0.00106	1850
703007D2014	38.9	0.059	310	2.36E-05	0.572	0.00105	1850
70280NB2014	37.5	0.0569	297	2.28E-05	0.551	0.00101	1780
60280ND2018	37.4	0.0568	297	2.28E-05	0.551	0.001	1780
722003D2010	37	0.0562	292	2.24E-05	0.544	0.000999	1770
71250ND1018	36.5	0.0555	288	2.22E-05	0.536	0.000987	1770
702507B2014	36.1	0.0548	286	2.19E-05	0.531	0.000971	1720
77042NB2014	36	0.0547	284	2.19E-05	0.531	0.000964	1710
70300ND2010	36.1	0.0549	284	2.19E-05	0.532	0.000965	1710
60250NB2014	35.7	0.0542	283	2.17E-05	0.525	0.000959	1690
38250ND2014	35.6	0.0542	279	2.16E-05	0.526	0.000948	1690
702507D2010	35.6	0.0542	279	2.16E-05	0.525	0.000952	1690
77040ND2014	35.3	0.0536	277	2.14E-05	0.52	0.000943	1670
71250NB1014	35.2	0.0535	277	2.14E-05	0.519	0.000941	1680
77042ND2010	35	0.0532	274	2.12E-05	0.515	0.000935	1660
77045ND4010	34.8	0.053	273	2.11E-05	0.514	0.000927	1650
77040ND4010	34.4	0.0524	268	2.09E-05	0.509	0.000911	1630
77038NB2014	34.1	0.052	267	2.08E-05	0.504	0.000904	1620
77040ND4014	34.2	0.0521	266	2.08E-05	0.507	0.000904	1620
60250ND2014	33.8	0.0514	266	2.05E-05	0.499	9.00E-04	1600
702507D2014	33.9	0.0517	264	2.06E-05	0.501	9.00E-04	1610
77042ND4010	33.7	0.0514	262	2.04E-05	0.498	0.000892	1590
70250ND2018	33.6	0.0512	262	2.04E-05	0.496	0.000892	1590
71200NB1014	33.3	0.0507	258	2.02E-05	0.492	0.000881	1580
70250RB2014	32.9	0.0503	255	2.01E-05	0.489	0.000867	1560
70250RD2014	32.4	0.0495	252	1.97E-05	0.479	0.000859	1540
77038ND2014	32.6	0.0498	250	1.98E-05	0.484	0.000855	1540
70250RD2010	32.3	0.0493	249	1.96E-05	0.479	0.000847	1530
702007B2014	31.6	0.0484	242	1.92E-05	0.47	0.000826	1490
70250NB2014	31.5	0.0483	242	1.92E-05	0.468	0.000827	1500
70210NB2014	31.5	0.0482	242	1.91E-05	0.468	0.000824	1490
70250ND2014	31.2	0.0477	241	1.89E-05	0.463	0.00082	1480
70210RB2014	31.1	0.0476	239	1.89E-05	0.462	0.000815	1470
73100NB0514	30.4	0.0465	238	1.87E-05	0.456	0.00079	1460
71150ND1018	31.3	0.048	237	1.90E-05	0.466	0.000817	1500
70200RB2014	30.7	0.047	234	1.86E-05	0.456	0.000801	1450
70250ND2010	30.7	0.0471	234	1.86E-05	0.457	0.000801	1450
71150NB1014	30.4	0.0467	230	1.85E-05	0.455	0.000786	1440
70200NB2014	29.9	0.0459	228	1.82E-05	0.446	0.000778	1420
70200ND2014	29.6	0.0455	224	1.80E-05	0.442	0.000769	1400
70200ND2010-A5	29.4	0.0452	221	1.79E-05	0.44	0.000758	1390
70210ND2010	29.2	0.0449	219	1.77E-05	0.437	0.000752	1370
70200ND2010	28.5	0.0438	213	1.73E-05	0.426	0.000733	1340
71150ND1010	28.3	0.0436	210	1.72E-05	0.425	0.000719	1330
70150ND2010-A5	27.4	0.0423	201	1.66E-05	0.412	0.000694	1290
70150NB2014	26	0.0401	192	1.58E-05	0.391	0.000659	1220
70150ND2014	26	0.0401	191	1.57E-05	0.39	0.00066	1220



70150ND2010	24.3	0.0377	174	1.47E-05	0.368	0.000603	1130
73050NB0514	23.5	0.0367	174	1.47E-05	0.359	0.000583	1140
73050ND0510	22.5	0.0353	164	1.40E-05	0.345	0.000553	1090
70100ND2010	22.6	0.0353	160	1.37E-05	0.344	0.000556	1060
24025ND0514	18.4	0.0292	128	1.13E-05	0.282	0.000455	951
24020ND0514	17.6	0.0279	124	1.09E-05	0.274	0.000419	853
24015NB0514	16.8	0.0267	116	1.04E-05	0.262	0.000392	815
24020NB0518	16.2	0.026	108	1.01E-05	0.255	0.000375	807

b) Inventory Metrics:

Indicator/L CI Metric	TPE	RE	NR E	NR R	RR	WD P	LFW	LFHW	CBW C	CWW C	CHW	CNH W
Unit	MJ- Eq	MJ- Eq	MJ- Eq	kg	m3	m3	kg waste	kg waste	m3	m3	kg	kg
Minimum	876	24.6	859	22.2	0.00142	14.4	15.3	0.00135	0.262	6.35E-05	0.0149	0.747
Maximum	2480	79.1	2400	62.9	0.00535	7.06	37.3	0.003	0.207	6.35E-05	0.0149	0.747
Mean	1740	54.8	1680	44	0.00356	8.54	28.1	0.00229	0.226	6.35E-05	0.0149	0.747
Median	1750	55.3	1690	44.5	0.00363	7.57	28.1	0.00228	0.21	6.35E-05	0.0149	0.747
770451D4010	2480	79.1	2400	62.9	0.00535	7.06	37.3	0.003	0.207	6.35E-05	0.0149	0.747
723003D2014	2350	76.3	2270	59.5	0.00519	7.61	34.9	0.00285	0.204	6.35E-05	0.0149	0.747
60300ND1010	2180	74.3	2100	55	0.0051	0.285	33.6	0.00264	0.147	6.35E-05	0.0149	0.747
60250NB0514	2270	73.4	2190	57.4	0.00512	16	33.4	0.00282	0.3	6.35E-05	0.0149	0.747
722503D2014	2300	73.2	2230	58.5	0.00511	8.05	34	0.00278	0.205	6.35E-05	0.0149	0.747
703507D2010	2270	73.2	2210	57.7	0.00488	6.91	35.4	0.00284	0.232	6.35E-05	0.0149	0.747
723003D2010	2270	73.1	2180	57.4	0.00498	9.62	33.8	0.00278	0.191	6.35E-05	0.0149	0.747
40250NB1014	2200	71.7	2120	55.8	0.00499	11.3	32.2	0.00266	0.251	6.35E-05	0.0149	0.747
60250ND0514	2210	71.4	2140	56.1	0.00485	15.7	32.8	0.00276	0.294	6.35E-05	0.0149	0.747
722503B2014	2170	70.3	2100	55	0.00469	7.83	32.5	0.00266	0.206	6.35E-05	0.0149	0.747
70350NB2014	2180	70.1	2100	55.1	0.00476	7.38	33.6	0.00271	0.239	6.35E-05	0.0149	0.747
19050ND2010	2200	69.9	2120	55.4	0.00469	7.86	33.7	0.00273	0.228	6.35E-05	0.0149	0.747
722503D2010	2100	67.1	2040	53.3	0.00448	8.18	31.6	0.00259	0.196	6.35E-05	0.0149	0.747



<b>70300NB2014</b>	2050	66.4	1970	51.6	0.00442	7.7	32	0.00258	0.235	6.35E-05	0.0149	0.747
<b>70350ND2010</b>	2090	66.1	2020	52.9	0.00456	7.4	32.6	0.00264	0.226	6.35E-05	0.0149	0.747
<b>703007D2014</b>	2030	64.4	1970	51.7	0.00433	7.77	32.2	0.00261	0.216	6.35E-05	0.0149	0.747
<b>70280NB2014</b>	1960	62.8	1890	49.5	0.00421	8.24	31.1	0.00253	0.21	6.35E-05	0.0149	0.747
<b>60280ND2018</b>	1960	62.4	1900	49.5	0.00413	8.24	31.1	0.00253	0.21	6.35E-05	0.0149	0.747
<b>722003D2010</b>	1950	60.3	1890	49.3	0.00418	7.52	30.6	0.00249	0.21	6.35E-05	0.0149	0.747
<b>77042NB2014</b>	1870	59.9	1820	47.5	0.00382	7.99	30	0.00244	0.23	6.35E-05	0.0149	0.747
<b>71250ND1018</b>	1940	59.9	1880	49.2	0.00398	8.23	30.3	0.00246	0.209	6.35E-05	0.0149	0.747
<b>60250NB2014</b>	1860	59.8	1800	47.1	0.00398	7.68	29.6	0.00248	0.223	6.35E-05	0.0149	0.747
<b>702507B2014</b>	1900	59.8	1830	48	0.00405	8.08	30	0.00244	0.234	6.35E-05	0.0149	0.747
<b>70300ND2010</b>	1880	59.5	1820	47.6	0.00401	7.84	30.1	0.00245	0.223	6.35E-05	0.0149	0.747
<b>702507D2010</b>	1860	59.4	1800	47	0.00391	7.82	29.8	0.00242	0.21	6.35E-05	0.0149	0.747
<b>77040ND2014</b>	1840	58.6	1780	46.5	0.00386	7.62	29.5	0.00239	0.205	6.35E-05	0.0149	0.747
<b>77042ND2010</b>	1830	58.5	1770	46.1	0.00387	7.48	29.3	0.00238	0.223	6.35E-05	0.0149	0.747
<b>38250ND2014</b>	1850	58.5	1800	46.8	0.00395	8.19	29.9	0.00243	0.203	6.35E-05	0.0149	0.747
<b>71250NB1014</b>	1840	58.5	1780	46.7	0.00397	8.54	29.4	0.00239	0.219	6.35E-05	0.0149	0.747
<b>77038NB2014</b>	1780	56.8	1720	44.9	0.00378	8.81	28.7	0.00235	0.224	6.35E-05	0.0149	0.747
<b>77040ND4010</b>	1790	56.7	1730	45.3	0.00379	8.38	29	0.00236	0.21	6.35E-05	0.0149	0.747
<b>77045ND4010</b>	1810	56.4	1750	45.9	0.0039	8.06	29.2	0.00237	0.217	6.35E-05	0.0149	0.747
<b>77042ND4010</b>	1750	55.9	1690	44.3	0.00365	8.03	28.4	0.00232	0.216	6.35E-05	0.0149	0.747
<b>77040ND4014</b>	1780	55.5	1720	45.2	0.00376	8.65	28.9	0.00236	0.205	6.35E-05	0.0149	0.747
<b>60250ND2014</b>	1750	55.3	1690	44.5	0.00363	7.57	28.1	0.00228	0.21	6.35E-05	0.0149	0.747
<b>70250ND2018</b>	1750	55.2	1700	44.2	0.00369	7.91	28.3	0.0023	0.225	6.35E-05	0.0149	0.747
<b>702507D2014</b>	1770	55.2	1720	44.6	0.00364	8.09	28.6	0.00233	0.228	6.35E-05	0.0149	0.747
<b>71200NB1014</b>	1740	54.8	1680	44	0.00356	8.54	28.1	0.00229	0.226	6.35E-05	0.0149	0.747
<b>70250RD2014</b>	1690	54.2	1640	42.9	0.00346	8.06	27.4	0.00223	0.222	6.35E-05	0.0149	0.747



<b>70250RB2014</b>	1720	53.5	1660	43.4	0.0036	9.01	28	0.00229	0.216	6.35E-05	0.0149	0.747
<b>77038ND2014</b>	1690	52.4	1630	42.8	0.00353	8.41	27.8	0.00227	0.225	6.35E-05	0.0149	0.747
<b>70250RD2010</b>	1680	51.6	1630	42.5	0.00355	8.66	27.5	0.00224	0.224	6.35E-05	0.0149	0.747
<b>702007B2014</b>	1640	51.1	1590	41.6	0.00334	9.02	27	0.00221	0.223	6.35E-05	0.0149	0.747
<b>70210NB2014</b>	1630	51.1	1590	41.5	0.00346	8.93	26.8	0.0022	0.223	6.35E-05	0.0149	0.747
<b>70250NB2014</b>	1640	51	1600	41.6	0.00341	8.73	27.1	0.00221	0.227	6.35E-05	0.0149	0.747
<b>70250ND2014</b>	1630	51	1570	41	0.00326	8.19	26.6	0.00217	0.225	6.35E-05	0.0149	0.747
<b>73100NB0514</b>	1610	50.3	1560	40.8	0.00332	15.1	24.9	0.00213	0.262	6.35E-05	0.0149	0.747
<b>71150ND1018</b>	1650	50.3	1590	41.5	0.00329	8.91	26.9	0.00221	0.215	6.35E-05	0.0149	0.747
<b>70200RB2014</b>	1590	50.2	1540	40.2	0.00328	8.4	26.3	0.00215	0.228	6.35E-05	0.0149	0.747
<b>70210RB2014</b>	1620	50.1	1560	40.9	0.0033	8.39	26.5	0.00217	0.227	6.35E-05	0.0149	0.747
<b>70250ND2010</b>	1590	49.9	1550	40.4	0.00316	8.65	26.4	0.00216	0.22	6.35E-05	0.0149	0.747
<b>71150NB1014</b>	1580	48.8	1520	39.8	0.00311	9.43	26.3	0.00216	0.225	6.35E-05	0.0149	0.747
<b>70200NB2014</b>	1550	47.8	1510	39.2	0.00316	9.07	25.8	0.00212	0.223	6.35E-05	0.0149	0.747
<b>70200ND2014</b>	1540	47.7	1490	38.8	0.00299	8.36	25.6	0.0021	0.227	6.35E-05	0.0149	0.747
<b>70200ND2010-A5</b>	1520	46.7	1470	38.4	0.00313	9.02	25.5	0.0021	0.21	6.35E-05	0.0149	0.747
<b>70210ND2010</b>	1510	46	1460	38.1	0.00302	8.45	25.4	0.00208	0.216	6.35E-05	0.0149	0.747
<b>70200ND2010</b>	1470	45.6	1430	37.3	0.00302	8.63	24.8	0.00204	0.22	6.35E-05	0.0149	0.747
<b>71150ND1010</b>	1460	43.9	1410	36.9	0.00289	9.62	24.8	0.00205	0.214	6.35E-05	0.0149	0.747
<b>70150ND2010-A5</b>	1410	42.9	1360	35.7	0.00278	9.16	24.2	0.002	0.22	6.35E-05	0.0149	0.747
<b>70150NB2014</b>	1340	41.4	1300	33.9	0.0027	8.89	22.9	0.00189	0.216	6.35E-05	0.0149	0.747
<b>70150ND2014</b>	1350	40.6	1300	34	0.00261	8.36	22.9	0.00188	0.228	6.35E-05	0.0149	0.747
<b>73050NB0514</b>	1250	37.1	1210	31.7	0.00231	15.3	21.1	0.00181	0.268	6.35E-05	0.0149	0.747
<b>70150ND2010</b>	1240	37	1200	31.3	0.00231	8.69	21.9	0.00181	0.215	6.35E-05	0.0149	0.747
<b>73050ND0510</b>	1200	35.5	1160	30.2	0.00223	15.3	20.3	0.00175	0.252	6.35E-05	0.0149	0.747
<b>70100ND2010</b>	1160	34.5	1120	29.2	0.00214	8.67	20.6	0.00171	0.219	6.35E-05	0.0149	0.747



<b>24025ND051</b> 4	104 0	29. 4	101 0	26. 3	0.0017 2	13.6	16.6	0.0014 4	0.223	6.35E- 05	0.014 9	0.747
<b>24020ND051</b> 4	932	27.1	903	23.7	0.0016 4	13.6	16.1	0.0014	0.223	6.35E- 05	0.014 9	0.747
<b>24015NB051</b> 4	894	25. 4	863	22. 6	0.0015 2	13.9	15.6	0.0013 6	0.294	6.35E- 05	0.014 9	0.747
<b>24020NB051</b> 8	876	24. 6	859	22.2	0.0014 2	14.4	15.3	0.0013 5	0.262	6.35E- 05	0.014 9	0.747

## ADDITIONAL ENVIRONMENTAL INFO

No regulated substances of very high concern are utilized on site.

## REFERENCES

### ASTM Standards:

- ASTM A36/A36M Standard Specification for Carbon Structural Steel
- ASTM A108 Standard Specification for Steel Bar, Carbon and Alloy, Cold-Finished
- ASTM A123/A123M Standard Specification for Zinc (Hot-Dip Galvanized) Coatings on Iron and Steel Products
- ASTM A153/A153M Standard Specification for Zinc Coating (Hot-Dip) on Iron and Steel Hardware
- ASTM A184 Standard Specification for Welded Deformed Steel Bar Mats for Concrete Reinforcement
- ASTM A307 Standard Specification for Carbon Steel Bolts, Studs, and Threaded Rod 60,000 PSI Tensile Strength
- ASTM A416/A416M Standard Specification for Steel Strand, Uncoated Seven-Wire for Prestressed Concrete
- ASTM A555/A555M Standard Specification for General Requirements for Stainless Steel Wire and Wire Rods
- ASTM A615/A615M Standard Specification for Deformed and Plain Carbon-Steel Bars for Concrete Reinforcement
- ASTM A666 Standard Specification for Annealed or Cold-Worked Austenitic Stainless Steel Sheet, Strip, Plate, and Flat Bar
- ASTM A706/A706M Standard Specification for Deformed and Plain Low-Alloy Steel Bars for Concrete Reinforcement
- ASTM A767/A767M Standard Specification for Zinc-Coated (Galvanized) Steel Bars for Concrete Reinforcement
- ASTM A775/A775M Standard Specification for Epoxy-Coated Steel Reinforcing Bars
- ASTM A820/A820M Standard Specification for Steel Fibers for Fiber-Reinforced Concrete
- ASTM A884/A884M Standard Specification for Epoxy-Coated Steel Wire and Welded Wire Reinforcement
- ASTM A934/A934M Standard Specification for Epoxy-Coated Prefabricated Steel Reinforcing Bars





- ASTM A1064/A1064M Standard Specification for Carbon-Steel Wire and Welded Wire Reinforcement, Plain and Deformed, for Concrete
- ASTM C33/C33M Standard Specification for Concrete Aggregates
- ASTM C94 Standard Specification for Ready-Mixed Concrete
- ASTM C150/C150M Standard Specification for Portland Cement
- ASTM C260/C260M Standard Specification for Air-Entraining Admixtures for Concrete
- ASTM C595 Standard Specification for Blended Hydraulic Cements
- ASTM C618 Standard Specification for Coal Fly Ash and Raw or Calcined Natural Pozzolan for Use in Concrete
- ASTM C979/C979M Standard Specification for Pigments for Integrally Colored Concrete
- ASTM C989/C989M Standard Specification for Slag Cement for Use in Concrete and Mortars
- ASTM C1017/C1017M Standard Specification for Chemical Admixtures for Use in Producing Flowing Concrete
- ASTM C1116/C1116M Standard Specification for Fiber-Reinforced Concrete
- ASTM C1157/C1157M Standard Performance Specification for Hydraulic Cement
- ASTM C1240 Standard Specification for Silica Fume Used in Cementitious Mixtures
- ASTM C1602/C1602M Standard Specification for Mixing Water Used in the Production of Hydraulic Cement Concrete
- ASTM G109 Standard Test Method for Determining Effects of Chemical Admixtures on Corrosion of Embedded Steel Reinforcement in Concrete Exposed to Chloride Environments
- ASTM C330/C330M Standard Specification for Lightweight Aggregates for Structural Concrete
- ASTM C494/C494M Standard Specification for Chemical Admixtures for Concrete

#### CSA Standards:

- CAN/CGSB-1.40 Anticorrosive Structural Steel Alkyd Primer
- CAN/CSA G30.18 Carbon steel bars for concrete reinforcement
- CAN/CSA A3000 Cementitious Materials Compendium
- CAN/CSA G40.20/G40.21 General requirements for rolled or welded structural quality steel / Structural quality steel
- CAN/CSA A23.1/A23.2 Concrete Materials and Methods of Concrete Construction/Test methods and Standard Practices for Concrete
- CAN/CSA A23.4 Precast concrete - Materials and construction
- CSA S806 Design and construction of building structures with fiber-reinforced polymers

#### ISO Standards:

- ISO 6707-1: 2014 Buildings and Civil Engineering Works - Vocabulary - Part 1: General Terms
- ISO 14021:1999 Environmental Labels and Declarations - Self-declared Environmental Claims (Type II Environmental Labeling)
- ISO 14025:2006 Environmental Labels and Declarations - Type III Environmental Declarations - Principles and Procedures



- ISO 14040:2006 Environmental Management - Life Cycle Assessment - Principles and Framework
- ISO 14044:2006 Environmental Management - Life Cycle Assessment - Requirements and Guidelines
- ISO 14067:2018 Greenhouse Gases - Carbon Footprint of Products - Requirements and Guidelines for Quantification
- ISO 14050:2009 Environmental Management - Vocabulary
- ISO 21930:2017 Sustainability in Building Construction - Environmental Declaration of Building Products

### EN Standards:

- EN 16757 Sustainability of construction works - Environmental product declarations - Product Category Rules for concrete and concrete elements
- EN 15804 Sustainability of construction works - Environmental product declarations - Core rules for the product category of construction products

### Other References:

- US EPA Waste Reduction Model (WARM), Fly Ash  
Chapter: <http://epa.gov/climatechange/wycd/waste/downloads/fly-ash-chapter10-28-10.pdf>
- American Concrete Institute (ACI) 211: Standard Practice for Selecting Proportions for Normal, Heavyweight, and Mass Concrete.
- ACI 318-14 Building Code Requirements for Structural Concrete and Commentary. American Concrete Institute. Farmington Hills, MI, USA available at <https://www.concrete.org/store/>
- Mather, B & Ozyildirim, C. (2002). SP-1(02) : Concrete Primer. American Concrete Institute: SP0102. American Concrete Institute. Farmington Hills, MI, USA available at <https://www.concrete.org/store/>
- NSF International (February 2019). Product Category Rules (PCR) for ISO 14025 Type III Environmental Product Declarations (EPDs) of Concrete v1.2.
- Product Category Rules for Preparing an Environmental Product Declaration for Precast Concrete (UN CPC 37550), ASTM International, March 2015. [https://www.astm.org/CERTIFICATION/DOCS/266.PCR\\_for\\_Precast\\_Concrete.pdf](https://www.astm.org/CERTIFICATION/DOCS/266.PCR_for_Precast_Concrete.pdf)
- USGBC LEED v4 for Building Design and Construction, 11 Jan 2019 available at <https://www.usgbc.org/resources/pcr-committee-process-resources-part-b>
- USGBC PCR Committee Process & Resources: Part B, USGBC, 7 July 2017 available at <https://www.usgbc.org/resources/pcr-committee-process-resources-part-b>.

